



352 DS AIREX 2V

ATEX certified for zone 1, 2, 21, 22 air operated industrial vacuum cleaner



Request a free
quotation

Download the
catalogue





352 DS AIREX 2V

ATEX certified for zone 1, 2, 21, 22 air operated industrial vacuum cleaner

352DS AIREX 2V is an ATEX certified industrial vacuum ideal for suction of medium quantities of dusts (both fine and toxic), guaranteeing maximum safety for workers

- Suitable for mixed wet dry applications
- Stainless steel construction
- Maintenance free double Venturi suction unit
- Integrated filter cleaning system
- Detachable container with possibility to use safety collection bags for hazardous dust.



Power	V	Aria compressa
Pression	bar	6
Compressed air supply	l/min	3000
Internal diameter compressed air supply	mm	10
Depression	mmH ₂ O	4180
Depression (continuous service)	mmH ₂ O	4180
Airflow max	m ³ /h	300
Surface	cm ²	20000
Filtration class (primary filter)	(IEC 60335-2-69)	M
Filter surface (HEPA filter)	cm ²	27000
Filtration class (HEPA filter)	(EN1822)	H14
Air load on primary filter	m ³ /m ² /h	150.00
Capacity	lt	35
Suction inlet diameter	mm	80
Sound level	dB(A)	76
Dimensions	cm	70 X 55 X 127 h.
ATEX Zone	(Directive 94/9/CE)	1, 2, 21, 22
Marking type	(Directive 94/9/CE)	II 2GD