DG 50 EXP Z22

Zone 22 ATEX certified industrial vacuum

Request a **free** quotation

Download the catalogue

2 ANNI garanzia

made in

All data mentioned in this document may change without notice.
Tutti i dati riportati in questo documento potrebbero variare senza preavviso.

www.delfinvacuums.it
delfin@delfinvacuums.it

DG 50 EXP Z22

Zone 22 ATEX certified industrial vacuum

DG30 EXP Z22 is apowerful, reliable and sturdy industrial vacuum: these features makes it a perfect investment for every industry, fromwood to plastic industry, fromconstructions to glass industry. Theantistatic filterand thecomplete earth groundingallows it to work continuously inATEX zones 22.

- Filter efficiency indicator.
- Extremely silent.
- Suitable for continuous duty 24/24.
- Double ATEX certification (machine and motor)
- Class M antistatic filter as standard
- Integrated pressure relief valve

All data mentioned in this document may change without notice.
Tutti i dati riportati in questo documento potrebbero variare senza preavviso.

www.delfinvacuums.it
delfin@delfinvacuums.it

Product tab

DG 50 EXP Z22

Power	V	400 3~
Frequency	Hz	50
Power	kW	4
Depression	mmH2O	3000
Depression (continuous service)	mmH2O	2300
Airflow max	m3/h	450
Surface	cm2	30000
Filtration class (primary filter)	(IEC 60335-2-69)	M
Filter surface (HEPA filter)	cm2	25000
Filtration class (HEPA filter)	(EN1822)	H14
Air load on primary filter	m3/m2/h	150.00
Capacity	lt	100
Suction inlet diameter	mm	80
Sound level	dB(A)	76
IP protection / Ins.Cl.	IP	65
Dimensions	cm	64 X 103 X 150 h.
Weight	kg	130
ATEX Zone	(Directive 94/9/CE)	22
Marking type	(Directive 94/9/CE)	II 3D

All data mentioned in this document may change without notice.
Tutti i dati riportati in questo documento potrebbero variare senza preavviso.

www.delfinvacuums.it
delfin@delfinvacuums.it