



## DG 50 EXP Z22

Zone 22 ATEX certified industrial vacuum



Request a free  
quotation

Download the  
catalogue



All data mentioned in this document may change without notice.  
*Tutti i dati riportati in questo documento potrebbero variare senza preavviso.*

[www.delfinvacuums.it](http://www.delfinvacuums.it)  
[delfin@delfinvacuums.it](mailto:delfin@delfinvacuums.it)





## DG 50 EXP Z22

Zone 22 ATEX certified industrial vacuum

DG30 EXP Z22 is a powerful, reliable and sturdy industrial vacuum: these features makes it a perfect investment for every industry, from wood to plastic industry, from constructions to glass industry. The antistatic filter and the complete earth grounding allows it to work continuously in ATEX zones 22.

- Filter efficiency indicator.
- Extremely silent.
- Suitable for continuous duty 24/24.
- Double ATEX certification ( machine and motor)
- Class M antistatic filter as standard
- Integrated pressure relief valve



Power	V	400 3~
Frequency	Hz	50
Power	kW	4
Depression	mmH2O	3000
Depressione ( continuous service)	mmH2O	2300
Range	m3/h	450
Surface	cm2	30000
Filtration class ( primary filter)	(IEC 60335-2-69)	M
Filter surface ( HEPA filter)	cm2	25000
Filtration class ( HEPA filter)	(EN1822)	H14
Air load on primary filter	m3/m2/h	150.00
Capacity	lt	100
Suction inlet diameter	mm	80
Sound level	dB(A)	76
IP protection / Ins.Cl.	IP	65
Dimensions	cm	64 X 103 X 150 h.
Weight	kg	130
ATEX Zone	(Directive 94/9/CE)	22
Marking type	(Directive 94/9/CE)	II 3D